



## Insulated container for very low temperatures

- Brand: MELFORM
- Country of origin: ITALY
- Customs code: 39231090
- Compatible with food contact
- Color: melange grey/blue
- Technology: rotational
- Warranty: 24 months
- Fully recyclable at the end of its service life
- Stackable and easy to move
- Ideal for dry ice deliveries in applications such as fresh/frozen food distribution for e-commerce, home delivery, last mile, grape harvesting and thermoregulation in food processes
- DrIcy containers are suitable for the containment of dry ice at a temperature of -78.5°C
- Containment capacity: approx. 50 kg of dry ice in 3 mm pellets, 40 kg in 10 mm pellets and 35 kg in 16 mm pellets
- **Each plastic material is subject to embrittlement when subjected to extremely low temperatures; Consequently, it is recommended to avoid the use of metal objects for the removal of any residual dry ice remaining on the bottom of the container**

### MANUFACTURING MATERIALS

<b>Polyethylene</b>	inner and outer walls of the container and lid; Suitable for food contact.	<b>Polyurethane</b>	insulating material between the walls of the container and the lid, free of CFCs and HCFCs.
<b>Silicone rubber</b>	gasket	<b>Stainless steel</b>	closing hooks.
<b>Galvanized steel</b>	hinge rod.		

Model	Code	EAN code	Ext. dim. (mm)	Int. dim. (mm)	Capacity (liters)	Weight (kg)
DrIcy 65	0065S001	8022949189402	860x535xh465	676x350xh275	65	20

## PRODUCT FEATURES

	Closure in stainless steel adjustable with eyelet for seal.		Flat bottom without grooves to reduce product residues
	Gasket easily replaceable.		Reinforced structure to ensure robustness. Low weight for easy handling.
	Ergonomic handles inserted on the body to facilitate safe handling.		Dedicated housings for stacking containers. Detail housings on the cover.
	Monobloc structure, without edges, joints and welds. Insulation only with CFC and HCFC free polyurethane foam.		Card holder for identification of the container or safety data sheet.
	Handling trolley in metal covered with polystyrene, with ABS corners. - 4 wheels diam. 100 mm in non-marking rubber - 2 swivel wheels - 2 wheels with brake		RFID systems for traceability
Overall heat transfer coefficient: <b>K=0.29 W/m<sup>2</sup>K</b>			

## ACCESSORIES

Model	Code	Ext. dim.(mm)	Weight (kg)
Handling trolley	THD65001	875x550xh170	6

