

Self powered refrigerated container KOALA GREEN 500

21/01/2025
Rev.2



ATP



The Koala Green refrigerated containers are powered by a LiFePO₄ battery, making them completely autonomous and independent from a vehicle. The removable battery can be recharged by connecting the Koala Green to the mains power(230V) or with an external charger after removing it from the refrigeration unit.

- Brand: MELFORM
- Country of origin: ITALY
- Customs code: 84181080
- ATP Certificate
- Compatible with food contact
- Colour: grey/blue
- Power supply and charging at 230Vac
- Technology: rotational moulding
- Warranty: 24 months
- Fully recyclable at the end of its operational life
- Available in version on wheels. Optionally available in basic version, on pallets or feet
- Available with **120Ah** LiFePO₄ battery

MANUFACTURING MATERIALS

Polyethylene	internal and external walls of the container and door; Suitable for food contact	Polyurethane	CFC- and HCFC-free insulating material between the container and door walls
Silicone rubber	gasket	Rubber and polyamide	wheels (rubber tread and polyamide core)
Galvanized steel	crankcase, hinge rods, hinge rod connection plates, wheel support	Stainless steel	handling handles, closing handle, rod door interior
Polypropylene	Hinges		











Via Savigliano 34 - 12030 Monasterolo di Savigliano (CN) - ITALY
Tel. +39 0172812600 - info@melform.com
www.melform.com

Model	Product code	EAN code	External dimensions (mm)	Internal dimensions (mm)	Capacity (litres)	Weight (Kg)
Top cooling unit, ventilated 0°C +10°C 120Ah battery Version with wheels	K500AFTVDYM1C	8022949223236	715x850xh1915	540x660xh1170	416	140
Top cooling unit, ventilated 0°C +40°C 120Ah battery Version with wheels	K500AFTVDZM1C	8022949223021				

Model	Ambient Temp. (°C)	Temp. Set Point (°C)	Battery life (h)
Koala Green 500 AF 0°C +10°C	30	0	10
Koala Green 500 AF 0°C +40°C			
Koala Green 500 AF 0°C +40°C	0	40	12

REFRIGERATION UNIT FEATURES

	The ventilation system ensures a higher speed of reaching and uniformity of temperature inside the container		Cable for 230Vac 50-60Hz power supply (standard equipment)
	The battery indicator displays: <ul style="list-style-type: none"> Battery Voltage (V) Current (A) Input/Output Power (W) Input/Output Ampere hours (Ah) consumed State of charge (%) Remaining autonomy (h) 		LiFePO4 battery with overcharge and deep discharge protection. Guaranteed for 2000 cycles with <u>>80% charge holding capacity</u>
	Temperature regulation and control with programmable digital thermostat		Removable battery for easy replacement and charging via special external power supply Battery storage limit temperature: -20°C / +60°C
	EVlink module with bluetooth interface available on request		Guaranteed refrigeration unit performance for ambient T-use: +10°C to +30°C Container (isothermal body) guaranteed for use: -30° to +100°C

Degree of accuracy: **+/-0.5°C**

Refrigerant gas: **R134a**

Rated Power Consumption: **1A**

Fuse: **4A**

Global heat transfer coefficient: **K=0.32 W/m2K**

Charging time battery life: **approx. 8/10 h**











Via Savigliano 34 - 12030 Monasterolo di Savigliano (CN) - ITALY

Tel. +39 0172812600 - info@melform.com

www.melform.com

PRODUCT FEATURES

	1 seat for housing the grid positioned 60 cm from the bottom of the container. Grid available on request		Stainless steel rod with 2 hooks integrated inside the door
	Door can be open up to 270° with latch – flap door		Stainless steel closing handle with release button; prepared for the use of an anti-tampering system
	Equipped with 4 rubber wheels with a diameter of 100mm (2 fixed and 2 swivel, one of which is equipped with brake) Wheel support plate integrated into the enclosure		Easily removable door sealing gasket
	Also available in the following versions: <ul style="list-style-type: none"> • BASIC • Pallet with galvanized steel frame at 4 feet of h 120mm • 4 galvanized steel feet h 130mm 		RFID systems for traceability

ACCESSORIES	Amperage	Weight (kg)	Dim. (mm)	Code
Stainless steel grid		3	550x650xh16	AEA008
Plastic folding grid		1,1	535x594xh20	PAPE0001
Plastic card holder			A5	RRI141
Floor/vehicle fixing kit for Basic version		2		RRI222
USB Data Logger, temperature range -30°C +70°C				AFG007
Battery charger	20 Ah			CHARGER20A
Battery KOALA GREEN	120 Ah			BATT120AH
Battery with charger for KOALA GREEN	120 Ah			BACH120AH